



## COMPACT CASSETTE 42QTD/38QUS - D8S



- **360° air flow:** guarantees uniform temperature distribution for perfect coverage of the space.
- **Fresh air inlet:** a ventilation motor can be installed in the external duct which, thanks to the indoor fan, introduces and increases the volume of fresh air.
- **Integrated discharge pump:** the discharge pump makes it possible to remove condensation up to a height of 750mm. It guarantees the installation of the drainage pipes in any space.



ENERGY CLASS



INVERTER TECHNOLOGY



ULTRA-QUIET



AUTO-DIAGNOSIS SYSTEM



RESTART FUNCTION



LOUVER POSITION MEMORY



AUTO SWING



FOLLOW ME



WEEKLY TIMER



INDEPENDENT DEHUMIDIFICATION



SLEEP MODE



AIR FLOW 360°



REFRIGERANT LEAK DETECTION



EASY INSTALLATION



R32

**Included**  
**RG67N****Optional**  
**KJR-120G2**

SYSTEM		12K cassette	18K cassette
Cooling Capacity	kW	3.50 (1.52~5.28)	5.30 (2.90~5.74)
Heating Capacity	kW	4.40 (1.03~5.57)	5.42 (2.37~6.10)
Heating Capacity to -7 °C	kW	4.10	4.70
Heating Capacity to -10 °C	kW	3.80	4.10
Heating Capacity to -15 °C	kW	3.60	3.70
Theoretical Thermal Load (PdesignC)	kW	3.50	5.30
Theoretical Thermal Load (Pdesignh)	kW	3.10	4.20
Theoretical Thermal Load (Pdesignh) mid-season	kW	3.50	5.30
SEER/SCOP (mid-season)/SCOP(warm season)	W/W	7.8 / 4.6 / 5.1	6.1 / 4.0 / 4.9
Energy Efficiency Class	-	A++ / A++ / A+++	A++ / A+ / A++
Indicative annual energy consumption	kWh	157 / 959 / 961	304 / 1470 / 1525
EER/COP	W/W	4.12 / 4.00	3.25 / 3.71
Nominal current draw (Cooling)	A	3.80	7.2
Nominal power draw (Cooling)	W	850	1630
Nominal current draw (Heating)	A	5.00	6.4
Nominal power draw (Heating)	W	1100	1460

OUTDOOR UNIT		38QUS012D8S	38QUS018D8S
Operating Range (Cooling)	°C	-15~50	-15~50
Operating Range (Heating)	°C	-15~24	-15~24
Power supply	-	220~240V / 50Hz / 1Ph	220~240V / 50Hz / 1Ph
Nominal current	A	10.0	13.5
Nominal power	W	2350	2950
Quantity of refrigerant (R32)	kg	0.87/0.588	1.15/0.776
Liquid/Gas pipes	mm (inch)	Φ6.35 / Φ9.52 (1/4" / 3/8")	Φ6.35 / Φ12.7 (1/4" / 1/2")
Standard pipe length	m	5	5
Min. pipe length	m	3	3
Max. pipe length	m	25	30
Max. drop	m	10	20
Additional refrigerant load	g/m	12	12
Sound power level	dB(A)	63	64
Sound pressure level	dB(A)	56	57
Air flow	m³/h	2000	2000
Weight (net/gross)	kg	34.7 / 37.5	33.7 / 36.6
Dimensions (LxWxH)	mm	800×333×554	800×333×554
Package (LxWxH)	mm	920×390×625	920×390×625

INDOOR UNIT		42QTD012D8S	42QTD018D8S-1
Nominal power	W	45	45
Max. nominal current	A	0.40	0.40
Sound power level	dB(A)	59	60
Sound pressure level (high/med/low)	dB(A)	42 / 39 / 36	45 / 42 / 36
Air flow (high/med/low)	m³/h	560 / 430 / 390	680 / 550 / 400
Unit weight (net/gross)	kg	16.5 / 19.0	16.5 / 19.5
Panel weight (net/gross)	kg	2.5 / 4.5	2.5 / 4.5
Unit dimensions (LxWxH)	mm	570×570×260	570×570×260
Unit package (LxWxH)	mm	662×662×317	662×662×317
Panel dimensions (LxWxH)	mm	647×647×50	647×647×50
Panel package (LxWxH)	mm	715×715×123	715×715×123